



DLF/DLH4301-B 43" TFT LCD, 3500 nits LED Backlight, 1920x1080

The DLF/DLH4301-B is a 43 inch industrial grade sunlight readable LCD, with high brightness 3500 nits, it produce sharp images, crisp text and lifelike colors. The Durapixel LED backlight technology ensures high reliability and low power consumption, suitable for outdoor application, kiosk, factory automation, military, transportation and gaming application.

Key Features

- High Brightness 3500 nits
- Sunlight Readable
- LED Backlight
- Low Power Consumption
- LCD Blacking Defect Free(Hi-Tni 110 °C)
- BL MTBF: 100,000 hours



Specifications

Model Name	DLF/DLH4301-B
Description	43" TFT LCD, 3500nits LED Backlight, 1920x1080
Screen Size	43"
Display Area (mm)	940.896(H) x 529.254(V)
Brightness	3500 cd/m ²
Resolution	1920x1080
Aspect Ratio	16:9
Contrast Ratio	1600 : 1
Pixel Pitch (mm)	0.49005(H) x 0.49005(V)
Pixel Pre Inch (PPI)	51
Viewing Angle	178°(H),178°(V)
Color Saturation (NTSC)	82%
Display Colors	16.7M
Response Time (Typical)	8ms
Panel Interface	LVDS
Input Interface	DVI-I, HDMI, DP
Input Power	AC100~240V
Power Consumption	157W(163W with AD Board)
OSD Key	4 Keys (Power Switch, Menu, +, -)
OSD Control	Brightness, Color, Contrast, Auto Turing, H/V Position...etc
Dimensions (mm)	968.2x 556.4x 44.8(T)
Bezel Size(U/B/L/R)	13.572/13.572/13.652/13.652 mm
Weight (Net)	11.6kg
Operating Temperature	-20 °C ~ 60 °C
Storage Temperature	-20 °C ~ 70 °C

DLF= Panel + LED Driving Board

DLH= Panel + LED Driving Board + AD Control Board


Specifications are subject to change without notice.
All brands or product names are trademarks or registered trademarks of their respective companies.





Mechanical Drawing


Outline Dimensions

Unit:mm





Not
1. Tolerance is $\pm 1.0\text{mm}$ unless noted



Connector View

Ordering Information

Part Number	Description
DLF4301-BNN-A11	43",3500nits,1920*1080,T2060,HTni,LID43C,3in1,V1
DLH4301-BNN-Q11	43",3500nits,1920*1080,T2060,HTni,LID43C,AD8891DHP,AC100~240V,3in1,V1

Optional Accessories

Part Number	Description
810618301010	CABLE,POWER,AC,1830mm USA type
810618301090	CABLE,POWER,AC,1830mm Europe type
810618301050	CABLE,POWER,AC,1830mm UK type
810618301170	CABLE,POWER,AC,1830mm Australia type
810618301031	CABLE,POWER,AC,1830mm Japan type

Customer request

Touch	SCT (Single-Touch), PCT (Multi-Touch)
Glass	Tempered glass, AR coating.....