

# SSF/SSH1236-Y

# 12.3" TFT LCD, 1200 nits LED Backlight , 1920x720 ultra-wide aspect ratio 16:6

The SSF/SSH1236-Y is a 12.3 inch color TFT-LCD display with special aspect ratio 16:6 and wide resolution 1920 x 720. It is Litemax's Spanpixel series product which designed for high brightness 1200 nits with power efficiency LED backlight. It provides LCD panel with specific aspect ratios and sunlight readable for digital signage, public transportation, exhibition hall, department store, and vending machine.

#### **Key Features**

- 12.3" Stretched LCD
- Ultra-Wide Screen (16 : 6)
- High Brightness 1200 nits
- LED Backlight
- Wide temperature (-30°C~85°C)
- Low Power Consumption
- BL MTBF: 30,000 hours



| Specifications  |  |  |
|---|--|--|
| SSF/SSH1236-Y   |  |  |
| 12.3" TFT LCD, 1200 nits LED backlight, 1920x720          |  |  |
| 12.3"   |  |  |
| 292.32(H) × 109.62(V)                                     |  |  |
| 1200 cd/m <sup>2</sup>                                    |  |  |
| 1920x720  |  |  |
| 16:6  |  |  |
| 1500 : 1  |  |  |
| 0.15225(H) x 0.15225(V)                                   |  |  |
| 167   |  |  |
| 176°(H),176°(V)   |  |  |
| 90%   |  |  |
| 16.7M   |  |  |
| 20ms  |  |  |
| LVDS  |  |  |
| HDMI, DP  |  |  |
| DC 12V  |  |  |
| 14W, 17W (with AD board)                                  |  |  |
| 4 Keys (Power Switch, Menu, +, -)                         |  |  |
| Brightness, Color, Contrast, Auto Turing, H/V Positionetc |  |  |
| 305.92(H) x 123.62(V) x 9.40(T)                           |  |  |
| 9.6/4.4/8.25/5.35 mm                                      |  |  |
| 0.32kg  |  |  |
| -30°C ~ 85 °C   |  |  |
| -40°C ~ 90 °C   |  |  |
|   |  |  |

SSF = Panel + LED Driving Board

SSH = Panel + LED Driving Board + AD Control Board


Specifications are subject to change without notice.

All brands or product names are trademarks or registered trademarks of their respective companies.


### **Mechanical Drawing**

### **Outline Dimensions**

Unit:mm







| Ordering Information |   |  |
|----------------------|---|--|
| Part Number          | Description   |  |
| SSF1236-YNW-A11      | 12.3",1200nits,1920x720,T3085,MaxRGB,LID12B,10in1,V1                            |  |
| SSH1236-YNW-T11      | 12.3",1200nits,1920x720,T3085,MaxRGB, LID12B,AD68862HP,10in1,V1                 |  |
| Optional Accessories |   |  |
| Part Number          | Description   |  |
| 840612051212         | ADAPTER,AC/DC,12V/5A,60W.Power-Din-4P,CWT.G99-ABF060F-N022.Efficiency-level-6,R |  |
| 810618301010         | CABLE,POWER,AC,1830mm USA type  |  |
| 810618301050         | CABLE,POWER,AC,1830mm UK type   |  |
| 810618301170         | CABLE,POWER,AC,1830mm Australia type  |  |
| 810618301031         | CABLE,POWER,AC,1830mm Japan type  |  |
|                      |   |  |
| Customer request     |   |  |
| Touch                | PCT (Multi-Touch)   |  |
| Glass                | Tempered glass, AR coating  |  |